

#### Serviço Médio

Indicada para serviços médios de sucção e descarga. Temperatura de Trabalho: +5°C ~ +50°C (PVC).



DIÂMETRO NOMINAL	DIÂMETRO INTERNO	DIÂMETRO EXTERNO	PRESSÃO DE TRABALHO		PRESSÃO DE RUPTURA		VÁCUO	RAIO DE CURVATURA Trabalho - Mínimo 25°C	LANÇE
			25°C kgf/cm <sup>2</sup>	25°C lbf/pol <sup>2</sup>	25°C kgf/cm <sup>2</sup>	25°C lbf/pol <sup>2</sup>			
3/4"	19,0	24,0	8,0	114	24	341	760	200	25 / 50
1"	25,0	30,0	8,0	114	24	341	760	300	25 / 50
1.1/4"	31,8	37,0	6,7	95	20	284	760	425	25 / 50
1.1/2"	38,0	43,5	6,7	95	20	284	760	575	25 / 50
* 1.3/4"	45,0	51,6	6,0	85	18	256	760	650	25 / 50
2"	50,0	57,0	6,0	85	18	256	760	725	25 / 50
* 2.3/8"	60,0	68,5	6,0	85	18	256	760	850	25 / 50
2.1/2"	62,5	71,0	6,0	85	18	256	760	975	25 / 50
3"	74,5	83,0	4,7	66	14	199	760	1.075	25 / 50
4"	101,2	112,0	4,0	57	12	171	760	1.950	25 / 50
* 5"	127,0	138,6	3,0	43	9	128	680	2.050	15 / 30
* 6"	149,0	163,0	2,7	38	8	114	660	2.950	15 / 30

\* Fornecimento sob consulta

### Verde

#### Servicio Moderado

Para servicios moderados de succión y descarga. Temperatura del Trabajo: +5°C ~ +50°C (PVC).



DIÂMETRO NOMINAL	DIÂMETRO INTERIOR	DIÂMETRO EXTERIOR	PRESIÓN DE TRABAJO		PRESIÓN DE RUPTURA		VACÍO	RADIO DE CURVATURA Trabajo - Mínimo 25°C	LARGO
			25°C kgf/cm <sup>2</sup>	25°C lbf/pol <sup>2</sup>	25°C kgf/cm <sup>2</sup>	25°C lbf/pol <sup>2</sup>			
3/4"	19,0	24,0	8,0	114	24	341	760	200	25 / 50
1"	25,0	30,0	8,0	114	24	341	760	300	25 / 50
1.1/4"	31,8	37,0	6,7	95	20	284	760	425	25 / 50
1.1/2"	38,0	43,5	6,7	95	20	284	760	575	25 / 50
1.3/4"	45,0	51,6	6,0	85	18	256	760	650	25 / 50
2"	50,0	57,0	6,0	85	18	256	760	725	25 / 50
2.3/8"	60,0	68,5	6,0	85	18	256	760	850	25 / 50
2.1/2"	62,5	71,0	6,0	85	18	256	760	975	25 / 50
3"	74,5	83,0	4,7	66	14	199	760	1.075	25 / 50
4"	101,2	112,0	4,0	57	12	171	760	1.950	25 / 50
5"	127,0	138,6	3,0	43	9	128	680	2.050	15 / 30
6"	149,0	163,0	2,7	38	8	114	660	2.950	15 / 30

### Green

#### Medium Jobs

Recommended for medium jobs of suction and discharge. Work temperature: +5°C ~ +50°C (PVC).



NOMINAL DIAMETER	INTERNAL DIAMETER	EXTERNAL DIAMETER	WORK PRESSURE		BURST PRESSURE		VACUUM	BEND RADIUS Minimum Working 25°C	LENGTH
			25°C kgf/cm <sup>2</sup>	25°C psi	25°C kgf/cm <sup>2</sup>	25°C psi			
3/4"	19,0	24,0	8,0	114	24	341	760	200	25 / 50
1"	25,0	30,0	8,0	114	24	341	760	300	25 / 50
1.1/4"	31,8	37,0	6,7	95	20	284	760	425	25 / 50
1.1/2"	38,0	43,5	6,7	95	20	284	760	575	25 / 50
1.3/4"	45,0	51,6	6,0	85	18	256	760	650	25 / 50
2"	50,0	57,0	6,0	85	18	256	760	725	25 / 50
2.3/8"	60,0	68,5	6,0	85	18	256	760	850	25 / 50
2.1/2"	62,5	71,0	6,0	85	18	256	760	975	25 / 50
3"	74,5	83,0	4,7	66	14	199	760	1.075	25 / 50
4"	101,2	112,0	4,0	57	12	171	760	1.950	25 / 50
5"	127,0	138,6	3,0	43	9	128	680	2.050	15 / 30
6"	149,0	163,0	2,7	38	8	114	660	2.950	15 / 30